

Dear Customer

This Teal compact classic Hand wash is supplied with 2 wire voltage sensing electronic control. The unit should be connected direct to the main vehicle battery without external switches.

Once connected a red LED will be continuously illuminate, but the unit will not draw power **UNTIL** the vehicle is running. The switch in/out values are typically:

12V unit:	On at 13.8-14V	Off at 12.5V.
24V unit:	On at 26.6V	Off at 25.5V

When installing use the fuse supplied in the positive line, and keep the wires short and the connections tight.

In the event of no water, the LED will flash and power will be locked out.  
To reset refill with water and remove and replace the fuse.

**12V 20A FUSE 24V 15A FUSE**  
**Black wire 4mm to chassis / earth**  
**Red wire 4mm with fuse to battery**

**Volt sensing ~ No extra switches req'd**  
**Keep wires short to reduce voltage drop**  
**Connect to main battery not auxiliary**  
**Fill with water before starting engine**

---

## **USER INSTRUCTIONS**

**Clean regularly using bleach solution**  
**Spray head can be removed to clean**  
**A flashing LED indicates safety lock out**  
**To reset, refill, remove and replace fuse**

**NOT DRINKING WATER**  
**TEAL PATENTS LTD**  
**TEL: +44(0)121 770 0593**